

WHAT IS CLAIMED IS:

1. An information processing apparatus provided with an input system utilizing a stroboscope, comprising:

a stroboscope;

5 an imaging means for imaging an object at a light-emission and at a non-light-emission of said stroboscope to output an image signal at light-emission and an image signal at non-light emission;

a first means for calculating a part or all of information of a position, a size, a velocity, an acceleration, a moving path pattern of said object on the basis of differences
10 between a plurality of said image signals at light-emission and a plurality of said image signals at non-light emission; and

a second means for performing information processing on the basis of the information calculated by said first means.

2. An information processing apparatus according to claim 1, wherein said first
15 means includes a determination means for determining whether or not said information is coincident with a predetermined condition.

3. An information processing apparatus according to claim 2, wherein said first means further includes a valid input detecting means for detecting only a valid information out of said information on the basis of the determination result by said
20 determination means, and transmitting to said second means as the valid information being performed.

4. An information processing apparatus according to any one of claims 1 to 3, wherein said first means includes a distance calculating means for calculating a distance between said object and said imaging means from the information indicative of a size of
25 said object.

5. An information processing apparatus according to any one of claims 1 to 4, wherein said first means includes an analyzing means for analyzing information obtained from a difference between said image signal at light-emission and said image signal at non-light emission to extract a shape of said object, and

5 an angle calculating means for calculating an angle between said object and said imaging means from said shape.

6. An information processing apparatus according to claim 5, wherein the analysis by said analyzing means is for extracting predetermined two points within said object, and the calculation of the angle by said angle calculating means is for calculating an angle
10 between a line segment between the predetermined two points and a predetermined coordinate axis.

7. An information processing apparatus according to any one of claims 1 to 6, wherein a time interval of the light-emission of said stroboscope is freely settable.

8. An information processing apparatus according to any one of claims 1 to 6,
15 wherein a length of the light-emission and a length of the non-light-emission of said stroboscope are freely configurable.

9. An information processing apparatus according to any one of claims 1 to 6, wherein an exposure period of said imaging means is freely configurable.

10. An information processing apparatus according to any one of claims 1 to 9,
20 wherein said object includes a reflective body.

11. An information processing apparatus according to any one of claims 1 to 10, wherein said stroboscope includes a light source for outputting a light having a specific wavelength range, and said imaging means responds to only said specific wavelength range.

25 12. An information processing apparatus according to claim 11, wherein said

imaging means includes a filter for passing only said light having a specific wavelength range and an imaging device for imaging an image formed by the light that passes through the filter.

13. An information processing apparatus according to claim 11, wherein said
5 imaging means includes an imaging device for imaging only the image formed by said light having a specific wavelength range.

14. An information processing apparatus according to any one of claims 1 to 13, wherein each of said first means and said second means is a process to be processed by a single or a plurality of processors.

10 15. An information processing apparatus according to any one of claims 1 to 14, wherein the information processing performed by said second means is an entertainment processing such as a game, etc.

16. A man-machine interface system provided with an input system by use of a stroboscope, comprising:

15 a stroboscope;

an imaging means for imaging an object at a light-emission and at a non-light-emission of said stroboscope to output an image signal at light-emission and an image signal at non-light emission;

20 a first means for calculating a part or all of information of a position, a size, a velocity, an acceleration, a moving path pattern of said object on the basis of differences between a plurality of said image signals at light-emission and a plurality of said image signals at non-light emission; and

a second means for performing information processing on the basis of the information calculated by said first means.

25